

Datasheet

2.5" SATA SSD

3TG6-P AES series

- 2.5" SATA III solution for industrial field
- High IOPS
- iSMART disk health monitoring
- AES-256 encryption
- End to end data path protection
- iData Guard for abnormal power failure
- iCell technology for data protection (optional)
- iPower Guard for protecting unstable start up and shut down



Introduction

Innodisk 2.5" SATA SSD 3TG6-P is SATA III 6Gb/s solid state disk, which delivers excellent performance, especially in random data transfer rate, and which offers reliability making it the ideal solution for a variety of applications, including embedded system, industrial computing, and enterprise field. 3TG6-P 2.5" SSD not only performs unmatched performance, but also designed with Innodisk owned technical knowhow to ensure the data integrity and highest levels of reliability.

Drawing

Technical drawing of a rectangular box with dimensions and detail callouts:

- Top View:**
 - Overall width: 60.30 ± 0.20
 - Overall height: 10.80 ± 0.10
 - Internal width: 4.80
 - Internal height: 2.00 ± 0.05
- Front View:**
 - Overall height: 10.80 ± 0.10
 - Internal height: 4.80
 - Internal width: 4.80
 - Internal depth: 2.00
- Side View:**
 - Overall width: 60.30 ± 0.20
 - Overall height: 10.80 ± 0.10
 - Internal width: 4.80
 - Internal height: 2.00 ± 0.05
- Detail A:**
 - 4-Min 50°
 - DEPT 116.1mm
 - 61.72
 - 1.50
 - 60.30
- Tolerance:** TOLERANCE: ± 0.30mm
- Unit:** UNIT

www.innodisk.com